

### EM-A1600SH WIDE FORMAT LAMINATING SYSTEM

Easymount Air<sup>®</sup> is a revolutionary product in the wide format lamination & mounting market.



#### KEY FEATURES

- **NEW** Swing-out arms for easier loading of laminate and film
- Pneumatic air pressure
- 10m/33ft a minute
- 30mm/1 $\frac{3}{16}$ " mounting thickness
- Variable speed control
- Foot pedal
- Reverse mode
- Multilingual control panel

#### GREAT FOR USE IN

- Sign makers
- Print finishers

#### IDEAL WHEN LAMINATING

- Posters, graphics and signs
- Mounting prints to board
- Pop-up displays
- Applying vinyls, tapes and adhesive films
- Outdoor signage
- and many more...

#### Design & Performance

The patented technology within the Easymount Air uses one of the most advanced concepts ever seen in a wide format laminator. Pneumatic air pressure controls the laminating rollers, allowing you to mount and laminate with incredible accuracy and speed. This new technology allows the roller to adjust to the exact thickness and pressure required, giving faster production times. The pneumatic air allows the roller to float down; ensuring Foamex and fluted boards are not crushed. When the rollers achieve the correct board thickness, the roller can be locked in place to keep the required gap, making board feeding more accurate. Mechanical wedges, often used to lock the roller by other pneumatic systems, are not required.

#### Specifications

#### EM-A1600SH

|                                |                           |
|--------------------------------|---------------------------|
| Laminating Speed (m/ft/min)    | 10m/33ft                  |
| Max. Width (mm/inches)         | 1600mm/63"                |
| Mounting Thickness (mm/inches) | 30mm/1 $\frac{3}{16}$ "   |
| Roller Diameter (mm/inches)    | 130mm/5"                  |
| Laminating Temperature (°C/F)  | 0-60°C/32-140°F           |
| Control Panel                  | Digital                   |
| Pressure Adjustment            | Pneumatic                 |
| Film Core (mm/inches)          | 77mm/3"                   |
| Power Supply AC (V-Hz)         | 220/240-50-60             |
| Power Consumption (W)          | 1500                      |
| Overall Dimensions (mm/inches) | 2190x650x1255mm/86x26x49" |
| Gross Machine Weight (Kg/lbs)  | 245Kg/540lbs              |
| Warranty                       | 1 year                    |



Patented pneumatic rollers 'float' down and will not crush soft materials like Correx<sup>®</sup>.



Front mandrel swings-out for easier loading of vinyl



Rear mandrel swings-out for easier loading of laminate