

## WIDE FORMAT LAMINATING SYSTEMS

Easymount® is designed to perform and built to last.



▲ EM-1600SH

### KEY FEATURES

- 6m/20ft a minute
- Variable speed control
- Foot pedal
- Reverse mode
- Multilingual control panel
- 25mm/1" mounting thickness

### GREAT FOR USE IN

- Sign makers
- Print finishers

### IDEAL WHEN LAMINATING

- Posters, graphics and signs
- Mounting prints to board
- Pop-up displays
- Applying vinyls, tapes and adhesive films
- Outdoor signage
- and many more...

### Design & Performance

The Easymount® laminators are designed to perform and built to last.

Their advanced features allow you to laminate and mount.

Designed in-house by Vivid, the Easymount® range gives your business extra capacity by allowing you to offer your customers a complete service that you previously had to outsource.

### Features

- Solid heavy duty construction
- Release liner take-up
- Adjustable rollers up to 20mm/0.8"
- Large rollers for even pressure
- Handy reverse mechanism
- Foot pedal for controlled operation

### Specifications

|                                | EM-1200SH                     | EM-1400SH                     | EM-1600SH                     | EM-2100SH                      |
|--------------------------------|-------------------------------|-------------------------------|-------------------------------|--------------------------------|
| Laminating Speed (m/ft/min)    | 6m/20ft                       | 6m/20ft                       | 6m/20ft                       | 6m/20ft                        |
| Max. Width (mm/inches)         | 1200mm/47"                    | 1400mm/55"                    | 1600mm/63"                    | 2100mm/83"                     |
| Mounting Thickness (mm/inches) | 25mm/ 1"                      | 25mm/ 1"                      | 25mm/ 1"                      | 25mm/ 1"                       |
| Roller Diameter (mm/inches)    | 112mm/4"                      | 112mm/4"                      | 130mm/5"                      | 130mm/5"                       |
| Laminating Temperature (°C/°F) | 0-60°C/32-140°F               | 0-60°C/32-140°F               | 0-60°C/32-140°F               | 0-60°C/32-140°F                |
| Control Panel                  | Digital                       | Digital                       | Digital                       | Digital                        |
| Pressure Adjustment            | Manual/Gauge                  | Manual/Gauge                  | Manual/Gauge                  | Manual/Gauge                   |
| Film Core (mm/inches)          | 77mm/3"                       | 77mm/3"                       | 77mm/3"                       | 77mm/3"                        |
| Power Supply AC (V-Hz)         | 220/240-50-60                 | 220/240-50-60                 | 220/240-50-60                 | 220/240-50-60                  |
| Power Consumption (W)          | 970                           | 1310                          | 1500                          | 1800                           |
| Overall Dimensions (mm/inches) | 1790x650x1255mm/<br>70x26x49" | 1990x650x1255mm/<br>78x26x49" | 2190x650x1255mm/<br>86x26x49" | 2650x650x1255mm/<br>104x26x49" |
| Gross Machine Weight (Kg/lbs)  | 185Kg/408lbs                  | 210Kg/463lbs                  | 245Kg/540lbs                  | 280Kg/617lbs                   |
| Warranty                       | 1 year                        | 1 year                        | 1 year                        | 1 year                         |