

REALISE STUNNING PRINT QUALITY WITH ADVANCED SECURITY



A large format solution for
print service providers in the
photographic and fine art markets.



- **Save ink costs**

Remaining media estimation prevents wasted ink by telling you exactly how much media you have left

- **Secure printing**

Restrict print connections and access by setting user security levels and individual passcodes

- **Smart software**

Intuitively control pre-print settings on-screen for precision output, with Professional Print

- **All media types/Auto media type detection**

A sensor detects the media, matches it with an internal database and automatically selects the media type

- **Borderless print**

Print various-sized borderless images from one roll size, with high margin adjustment accuracy

PRODUCT RANGE



imagePROGRAF PRO-2100



imagePROGRAF PRO-4100



imagePROGRAF PRO-6100

TECHNICAL SPECIFICATIONS

imagePROGRAF PRO-6100

TECHNOLOGY		
Printer Type	12 Colour 60"/1524mm	
Print Technology	Canon Bubblejet on Demand 12 colours integrated type (12 chips per print head x 1 print head)	
Print Resolution	2,400 x 1200 dpi	
Number of Nozzles	18,432 nozzles (1536 nozzles x 12 colour)	
Line Accuracy	±0.1% or less User adjustments necessary. Printing environment and media must match those used for the adjustments. CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only	
Nozzle Pitch	600 dpi x 2 includes Non-firing nozzle detection and compensation system	
Ink Droplet Size	minimum 4 pl per colour	
Ink Capacity	Sales Ink: 160ml/330ml/700ml Bundled Starter Ink: 330ml	
Ink Type	Pigment inks - Black, Matte Black, Cyan, Magenta, Yellow, Photo Cyan, Photo Magenta, Grey, Photo Grey, Red, Blue, Chroma Optimiser	
OS Compatibility	Microsoft Windows: 32 Bit, Vista, 7, 8, 8.1, 10 Server 2008, 64 Bit: Vista, 7, 8, 8.1, 10, Server 2008/R2, Server 2012/R2, Windows Server 2019 Apple Macintosh: OS X 10.10.5 - OS X 10.11, macOS 10.12 - macOS 10.14	
Printer Languages	SG Raster (Swift Graphic Raster), PDF (Ver.1.7), JPEG (Ver. JFIF 1.02)	
Standard Interfaces	USB A Port: USB Memory Direct Print for JPEG/PDF files USB B Port: Built-in Hi-Speed USB 2.0 Ethernet: 10/100/1000 base-T Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b *Please refer to user manual how to activate/deactivate the wireless LAN	
MEMORY		
Standard memory	3 GB	
Hard Drive	500GB (Encrypted HDD)	
PRINT TIME FOR A0 PAGE SIZE		
Media Type	Print Mode: Print Time	
Plain Paper	Print Mode Print Time Fast 1:37 min Standard 2:49 min	
Coated Paper	Print Mode Print Time Standard 2:49 min High Quality 5:35 min	
Glossy Photo Paper	Print Mode Print Time Standard 5:35 min High Quality 8:50 min	
MEDIA HANDLING		
Media Feed and Output	Upper Roll Paper: One Roll, Front-loading, Front Output Lower Roll Paper: One Roll, Front-loading, Front Output Cut Sheet: Front-loading, Front Output (Manual feed using media locking lever)	
Media Width	Roll paper: 152.4 -1524 mm Cut sheet: 152.4 - 1524 mm	
Media Thickness	Roll/Cut: 0.07 - 0.8 mm	
Minimum Printable Length	203.2 mm	
Maximum Printable Length	Roll paper: 18 m (Varies according to the OS and application) Cut sheet: 1.6 m	
Maximum Media Roll Diameter	170 mm	
Media Core Size	Internal diameter of roll core: 2"/3"	
Margins Recommended area	Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm	
		Margins Printable area
		Roll paper: Top: 3 mm, Bottom: 3 mm, Side: 3 mm Roll paper (borderless): Top: 0 mm, Bottom: 0 mm, Side: 0 mm
		Cut sheet: Top: 3 mm, Bottom: 20 mm, Side: 3 mm Roll Paper: Two rolls. Automatic switching is possible. Cut Sheet: 1 sheet
		Dual direction roll take up unit allowing print surface to be wound inside or outside of the roll
		515mm(JIS B2), 728mm(JIS B1), 1030mm(JIS B0), 594mm(ISO A1), 841mm(ISO A0), 10", 14", 17", 24", 36", 42", 44", 50", 54", 60", 257mm(JIS B4)*, 297mm(ISO A3)*, 329mm(ISO A3+)*, 420mm(ISO A2)*, 6", 8", 12", 16", 20", 22", 30", 300mm*, 500mm, 600mm, 800mm, 1000mm and custom roll width (152.4-1524mm) *Some environmental conditions may not produce the desired result
		Standard position: 1 sheet Flat position: A2 landscape, glossy paper less than 10 sheets, Coated paper less than 20 sheets (excludes strong curled condition)
		Media Feed Capacity
		1999 x 984 x 1168 mm (Basket Open) 1999 x 766 x 1168 mm (Basket Closed) 167 kg (including Roll Holder Set and Roll unit, excluding ink and print heads)
		Printer (Main unit with pallet): 2227 x 915 x 1022 mm 210 kg Roll Unit: 2133 x 562 x 461 mm 40 kg
		Media Take-up roll unit
		Borderless Printing Width (Roll Only)
		Maximum number of delivered prints
		1999 x 984 x 1168 mm (Basket Open) 1999 x 766 x 1168 mm (Basket Closed) 167 kg (including Roll Holder Set and Roll unit, excluding ink and print heads)
		DIMENSIONS AND WEIGHT
		1999 x 984 x 1168 mm (Basket Open) 1999 x 766 x 1168 mm (Basket Closed) 167 kg (including Roll Holder Set and Roll unit, excluding ink and print heads)
		Packaged Dimensions WxDxH (mm) and Weight (Kg)
		1999 x 984 x 1168 mm (Basket Open) 1999 x 766 x 1168 mm (Basket Closed) 167 kg (including Roll Holder Set and Roll unit, excluding ink and print heads)
		POWER AND OPERATING REQUIREMENTS
		AC 100-240V (50-60Hz) Operation: 103 W or less Sleep mode: 3.6W or less Default setting for the time to enter the Sleep mode: Approx. 5 Minutes Power off: 0.3 W or less
		Temperature: 15-30°C, Humidity: 10-80% RH (no dew condensation)
		Operation: 50 dB (A) (Glossy paper, Print priority: Standard) Standby: 35 dB (A) or less Operation: 6.7 Bel's or less (Glossy paper, Image, Print priority: Standard) (Measured on ISO 7779 standard)
		Europe: CE mark, Russia: EAC
		Operating Environment
		TUV, CB
		Acoustic Noise (Power/Pressure)
		Regulations
		Certificates
		WHAT'S INCLUDED
		What's in the Box?
		Printer, 1print heads, 3 inch paper core attachment, Power Cable, 1 set of starter ink tanks, Set up guide, Safety/Standard Environment leaflet, User software CD-ROM (Win), PosterArtist Lite CD-ROM, EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet
		Software Included
		imagePROGRAF PRO Printer Driver, Print Plug-In for Office, Quick Utility Toolbox and PosterArtist Lite Other software available as Download from Web.
		OPTIONS
		Optional Items
		2/3" Roll Holder: RH2-66 Roll Unit: RU-63
		CONSUMABLES
		User Replaceable Items
		Ink Tank: PFI-100 (160ml), PFI-1300 (330ml), PFI-1700 (700ml) Print Head: PF-10 Cutter Blade: CT-07 Maintenance Cartridge: MC-30



Disclaimer
Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.TM and [®]: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.

