

imagePROGRAF
PRO-6100S

FAST AND SECURE HIGH- DEFINITION PRINTING FOR MAXIMUM VISUAL IMPACT



Est. 1991
DESIGNSUPPLY 
supporting creativity

An 8-colour large format device
for exceptional quality photo,
graphic and poster printing.



- **Passcode printing**

Prevent printouts being taken away by setting individual user access permissions

- **High performance**

Fast and efficient printing is delivered by automatic media feeding and media type selection

- **Borderless print**

Print various-sized borderless images from one roll size, with high margin adjustment accuracy

- **Image optimisation**

Accurate colour expression, improved gradation and increased sharpness deliver high image quality

- **Smooth workflows**

Save time by storing frequently-used print tasks and viewing image details on-screen

PRODUCT RANGE



imagePROGRAF PRO-4100S



imagePROGRAF PRO-6100



imagePROGRAF PRO-6100S

Canon

TECHNICAL SPECIFICATIONS

imagePROGRAF PRO-6100S

TECHNOLOGY		
Printer Type	8 Colour 60"/1524mm	
Print Technology	Canon Bubblejet on Demand 12 colours integrated type (12 chips per print head x 1 print head)	
Print Resolution	2,400 x 1200 dpi	
Number of Nozzles	18,432 nozzles (1536 nozzles x 4 colours, 3072 nozzles x 4 colours)	
Line Accuracy	±0.1% or less User adjustments necessary. Printing environment and media must match those used for the adjustments. CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only	
Nozzle Pitch	600 dpi x 2 includes Non-firing nozzle detection and compensation system	
Ink Droplet Size	minimum 4 pl per colour	
Ink Capacity	Sales Ink: 160ml/330ml/700ml Bundled Starter Ink: 330ml	
Ink Type	Pigment inks - Black, Matte Black, Cyan, Magenta, Yellow, Photo Cyan, Photo Magenta, Grey	
OS Compatibility	Microsoft Windows: 32 Bit, Vista, 7, 8, 8.1, 10 Server 2008, 64 Bit: Vista, 7, 8, 8.1, 10, Server 2008/R2, Server 2012/R2, Windows Server 2019 Apple Macintosh: OS X 10.10.5 - OS X 10.11, macOS 10.12 - macOS 10.14	
Printer Languages	SG Raster (Swift Graphic Raster), PDF (Ver.1.7), JPEG (Ver. JFIF 1.02)	
Standard Interfaces	USB A Port: USB Memory Direct Print for JPEG/PDF files USB B Port: Built-in Hi-Speed USB 2.0 Ethernet: 10/100/1000 base-T Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b *Please refer to user manual how to activate/deactivate the wireless LAN	
MEMORY		
Standard memory	3 GB	
Hard Drive	500GB (Encrypted HDD)	
PRINT TIME FOR A0 PAGE SIZE		
Media Type	Print Mode: Print Time	
Plain Paper	Print Mode Print Time Fast 1:21 min Standard 2:24 min	
Coated Paper	Print Mode Print Time Standard 2:24 min High Quality 5:34 min	
Glossy Photo Paper	Print Mode Print Time Standard 4:44 min High Quality 5:34 min	
MEDIA HANDLING		
Media Feed and Output	Upper Roll Paper: One Roll, Front-loading, Front Output Lower Roll Paper: One Roll, Front-loading, Front Output Cut Sheet: Front-loading, Front Output (Manual feed using media locking lever)	
Media Width	Roll paper: 152.4 -1524 mm Cut sheet: 152.4 - 1524 mm	
Media Thickness	Roll/Cut: 0.07 - 0.8 mm	
Minimum Printable Length	203.2 mm	
Maximum Printable Length	Roll paper: 18 m (Varies according to the OS and application) Cut sheet: 2133.6mm	
Maximum Media Roll Diameter	170 mm	
Media Core Size	Internal diameter of roll core: 2"/3"	
Margins Recommended area	Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm	
		Margins Printable area
		Roll paper: Top: 3 mm, Bottom: 3 mm, Side: 3 mm Roll paper (borderless): Top: 0 mm, Bottom: 0 mm, Side: 0 mm Cut sheet: Top: 3 mm, Bottom: 20 mm, Side: 3 mm Roll Paper: Two rolls. Automatic switching is possible. Cut Sheet: 1 sheet
		Dual direction roll take up unit allowing print surface to be wound inside or outside of the roll
		515mm(JIS B2), 728mm(JIS B1), 1030mm(JIS B0), 594mm(JIS A1), 841mm(ISO A0), 10", 14", 17", 24", 36", 42", 44", 50", 54", 60", 257mm(JIS B4), 297mm(ISO A3"), 329mm(ISO A3+), 420mm(ISO A2"), 6", 8", 12", 16", 20", 22", 30", 300mm*, 500mm, 600mm, 800mm, 1000mm and custom roll width (152.4-1524mm) *Some environmental conditions may not produce the desired result
		Standard position: 1 sheet Flat position: A2 landscape, glossy paper less than 10 sheets, Coated paper less than 20 sheets (excludes strong curled condition)
		Media Feed Capacity
		Media Take-up roll unit
		Borderless Printing Width (Roll Only)
		Maximum number of delivered prints
		DIMENSIONS AND WEIGHT
		Physical Dimensions WxDxH (mm) and Weight (Kg)
		Packaged Dimensions WxDxH (mm) and Weight (Kg)
		POWER AND OPERATING REQUIREMENTS
		Power Supply
		Power Consumption
		Operating Environment
		Acoustic Noise (Power/Pressure)
		Regulations Certificates
		WHAT'S INCLUDED
		What's in the Box?
		Software Included
		OPTIONS
		Optional Items
		CONSUMABLES
		User Replaceable Items
		Disclaimer
		Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. TM and [®] : All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.
		Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.
		Ink Tank: PFI-1100 (160ml), PFI-1300 (330ml), PFI-1700 (700ml) Print Head: PF-10 Cutter Blade: CT-07 Maintenance Cartridge: MC-30

