

# imagePROGRAF GP-200

## MAXIMISE YOUR PRINT MARKETING POTENTIAL WITH VIBRANT, EYE-CATCHING POSTER PRODUCTION



A compact, large format printer with newly developed fluorescent pigment ink for easy, high impact poster design, ideal for maximising sales and profits from retail and hospitality marketing.



- **Vivid colours**

Print eye-catching posters every time with advanced spot colour accuracy and fluorescent colour expression using newly developed fluorescent pink ink

- **Easy poster creation**

Create attractive and impactful marketing materials with PosterArtist 3.4, featuring new templates and built-in stock photo service, helping you produce stylish posters for any purpose

- **Professional finish**

High-precision paper edge detection supports free-size borderless printing for all paper roll sizes, making it easy to create borderless posters without cutting a printout

- **Direct to print**

Built in HDD allows for convenient and efficient printing of the saved data, also PDF and JPEG file can be printed from a USB memory without connecting to a PC

- **Compact design**

Maximise available office space with a small footprint printer that fits flat against the wall to offer full front usability, perfect for smaller offices

- **Security assured**

Have complete confidence in the security of your printouts with PIN-accessed Security Print feature

### PRODUCT RANGE



imagePROGRAF GP-300



imagePROGRAF GP-4000



imagePROGRAF GP-2000

**Canon**

Est. 1991  
**DESIGNSUPPLY**   
supporting creativity

# TECHNICAL SPECIFICATIONS

# imagePROGRAF GP-200

<b>TECHNOLOGY</b>			
Printer Type	6 Colour 24"	Borderless Printing Width (Roll Only)	[Recommended] 515 mm (JIS B2), 594 mm (ISO A1), 10", 14", 17", 24"
Print Technology	Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head)	[Printable] 257 mm (JIS B4), 297 mm (ISO A3), 329 mm (ISO A3+), 420 mm (ISO A2), 8", 12", 15", 16", 18", 20", 22", 300 mm, 500 mm, 600 mm, and custom roll width (203.2 - 610 mm)	
Print Resolution	2,400 x 1,200 dpi	Maximum number of delivered prints	Standard position of the basket : 1 sheet
Number of Nozzles	Total : 15,360 nozzles MBK, BK, C, M, Y, FP : 2,560 nozzles each		
Line Accuracy	±0.1% or less User adjustments necessary. Printing environment and media must match those used for the adjustments. CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only		
Nozzle Pitch	1,200 dpi x 2 includes Non-firing nozzle detection and compensation system minimum 5 pl per colour	<b>DIMENSIONS AND WEIGHT</b>	982 x 870 x 1060 mm (Basket Open) 982 x 757 x 1060 mm (Basket Closed) 50 kg (Main Unit + Stand + Basket, including Roll Holder Set, excluding ink and print head)
Ink Droplet Size	Bundled Starter Ink : 90 ml (MBK, BK, C, M, Y, FP)	Physical Dimensions WxDxH (mm) and Weight (Kg)	Printer (Main unit with pallet) : 1152 x 913 x 705 mm 69 kg Stand + Basket : 1055 x 824 x 268 mm
Ink Capacity	Sales Ink : 130 ml, 300 ml	Packaged Dimensions WxDxH (mm) and Weight (Kg)	
Ink Type	Pigment inks : 6 colour MBK, BK, C, M, Y, FP	<b>POWER AND OPERATING REQUIREMENTS</b>	AC 100-240V (50-60Hz)
OS Compatability	Microsoft Windows 32 Bit : 7, 8.1, 10 Microsoft Windows 64 Bit : 7, 8.1, 10, Windows Server 2008R2, 2012, 2012R2, 2016, 2019 Apple Macintosh : macOS 10.13.6 - macOS 11	Power Supply	Operation : 71 W or less Sleep mode : 2.1 W or less
Printer Languages	PDF (Ver1.7), JPEG (Ver. JFIF 1.02)	Power Consumption	Default setting for the time to enter the Sleep mode : Approx. 5 Minutes Power off : 0.3 W or less
Standard Interfaces	USB A Port : USB Memory Direct Print for JPEG/PDF files USB B Port : Built-in Hi-Speed USB Ethernet : IEEE 802.3 10base-T, IEEE 802.3u 100base-TX / Auto-Negotiation, IEEE 802.3ab 1000base-T / Auto-Negotiation, IEEE 802.3x Full Duplex Wireless LAN : IEEE802.11n/IEEE802.11g/IEEE802.11b	Operating Environment	Temperature : 15-30°C, Humidity : 10-80% RH (no dew condensation)
	*Please refer to user manual how to activate/deactivate the wireless LAN	Acoustic Noise (Power/Pressure)	Pressure Operation : 49 dB (A) (Plain paper, Standard mode, Poster) (Measured on ISO7779 standard) Standby : 35 dB (A) or less
<b>MEMORY</b>	2GB Expansion slot : No	Regulations	Power Operation : 6.7 Belz (Plain paper, Standard mode, Poster) (Measured on ISO7779 standard)
Standard memory	500GB	Enviroment Certificates	Europe : CE mark, Other Countries : CB certification
Hard Drive			TUV, CB
<b>PRINTING SPEED</b>		<b>WHAT'S INCLUDED</b>	
Poster:		What's in the Box?	Printer, 1 print head, 1 roll holder (spool), 3 inch paper core attachment, Power Cable, 1 set of starter ink tanks, Set up guide, Printer Stand Setup Guide, Quick Guide, Safety/Standard Environment leaflet, User software CD-ROM (Win), PosterArtist Lite CD-ROM, EU Biocide Sheet, Important Information Sheet
Plain Paper (A1)	0:25 (Fast) 0:44 (Standard)	Software Included	imagePROGRAF GP Printer Driver and PosterArtist Lite Other software available as Download from Web.
Heavy coated Paper (A1)	0:55 (Fast) 1:22 (Standard)	OPTIONS	2/3" Roll Holder : RH2-28 Printer Stand : SD-24
Glossy photo Paper (A1)	3:28 (Standard) 5:18 (High Quality)	CONSUMABLES	Ink Tank : PFI-120 (130ml), PFI-320 (300ml) Print Head : PF-07 Cutter Blade : CT-08 Maintenance Cartridge : MC-31
<b>MEDIA HANDLING</b>		User Replaceable Items	
Media Feed and Output	Roll Paper : One Roll, Upper-loading, Front Output Cut Sheet : Upper-loading, Front Output (Manual feed using media locking lever)	<b>Disclaimer</b>	
Media Width	Roll paper : 203.2 mm - 610 mm Cut sheet : 203.2 mm - 610 mm		Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.
Media Thickness	Roll/Cut : 0.07 mm - 0.8 mm		
Minimum Printable Length	Roll paper : 203.2 mm Cut sheet : 279.4 mm		
Maximum Printable Length	Roll paper : 18 m (Varies according to the OS and application) Cut sheet : 1.6 m		
Maximum Media Roll Diameter	150 mm		
Media Core Size	Internal diameter of roll core : 2"/3"		
Margins Recommended area	Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm		
Margins Printable area	Roll paper : Top: 3 mm, Bottom: 3 mm, Side: 3 mm Roll paper (borderless print) : Top: 0 mm, Bottom: 0 mm, Side: 0 mm Cut sheet : Top: 3 mm, Bottom: 20 mm, Side: 3 mm		
Media Feed Capacity	Roll Paper : 1 roll Cut Sheet : 1 sheet		

