

General

Technology Inkjet	Local interface Hi-Speed USB 2.0	Wireless network 2.4GHz and 5GHz support
Memory 256MB	Wired network Fast ethernet	Mobile print Print from your mobile devices to your Brother printer
Control panel 6.8cm colour touchscreen LCD		

Print

Print speed (A4)⁹ 1-sided: 28ipm/ppm mono and colour 2-sided: 21ipm/ppm mono and colour	First print out time¹⁰ 4.6 seconds colour and 4.4 seconds mono	Resolution Up to 1200 x 4800dpi (horizontal and vertical)
Print (A3) 1-sided: Yes 2-sided: Yes	Quiet mode A mode to reduce the printing noise	

Printer functions

N-up printing³ Reduce up to 2, 4, 9 or 16 pages into just one page	Watermark printing⁴ Watermark your documents with predefined text or with your own user-defined messages	Booklet printing⁴ Print documents in A5 booklet format using automatic or manual 2-sided print
Poster printing⁴ Enlarge a single page into a poster using 4 or 9 pages	ID printing⁴ Add identification to your printed documents (date and time, short custom message or PC username)	Print profiles³ Store your favourite driver settings as profiles to easily recall them

Printer driver

Windows Windows 10 (32 and 64 bit editions) Windows 8 (32 and 64 bit editions) Windows 7 (32 and 64 bit editions) Windows Server 2019, 2016, 2012, 2012R2 and 2008R2 Windows Server 2008 (32 and 64 bit editions)	macOS 10.14.6/10.15.x/11	PostScript universal printer driver Driver for Windows that enables you to print to any network or locally connected Brother ink printer
	Linux CUPS, LPD/LPRng (i686 and x86_64)	
	PCL driver Generic PCL XL driver	
	ChromeOS Supports native ChromeOS printing	

Paper handling

Paper input²

Standard tray

250 sheets

Manual feed slot

1 sheet

ADF

50 sheets

Paper output²

100 sheets A4 | 50 sheets A3

Envelope printing

Yes from manual feed slot tray and standard tray

Media sizes

Standard tray

A4, LTR, EXE, A3, LGR, LGL, Folio, A5, A6, Photo (10 x 15cm), Indexcard (13 x 20cm), Photo-L (9 x 13cm), Photo-2L (13 x 18cm), Com-10, DL Envelope, Monarch, C5, Mexico Legal, India Legal

Manual feed slot

A4, LTR, EXE, A3, LGR, LGL, Folio, A5, A6, Photo (10 x 15cm), Indexcard (13 x 20cm), Photo-L (9 x 13cm), Photo-2L (13 x 18cm), Com-10, DL Envelope, Monarch, C5, Mexico Legal, India Legal

ADF

Width: 105 to 297.0 mm

Length: 148 to 431.8 mm

Scanner glass

Width: up to 297.0 mm

Length: up to 431.8 mm

Auto 2-sided

A4, LTR, A3, LGR, LGL, Folio, Mexico Legal, India Legal, EXE, A5

Mobile and web connectivity

Brother mobile connect⁵ (Android)

Print from, scan to, send faxes, preview received faxes, preview copies and check the machine status from an Android device

Brother mobile connect⁵ (iPad / iPhone)

Print from, scan to, send faxes, preview received faxes, preview copies and check the machine status from an iPad / iPhone

Apple AirPrint

Print from and scan to most common file types from any AirPrint enabled application

Brother print service plugin⁵

Print from an Android devices without a dedicated app.

MopriaTM 5

Print most common file types from MopriaTM supported Android devices

Media type and weights

Standard tray

Plain, inkjet, glossy, recycled 64-220g/m²

Manual feed slot

Plain, inkjet, glossy, recycled 64-220g/m² (260g/m² with Brother BP71 glossy paper only)

ADF

Plain and recycled paper 64-120g/m²

Auto 2-sided

Plain, recycled 64-120g/m²

Copy

Copy speed (A4)¹¹
1-sided: 25ipm/ppm mono and
16ipm/ppm colour

Copy (A3)
1-sided: Yes

First copy out time¹¹
5.0 seconds mono and
6.0 seconds colour

Resolution
Up to 600 x 600dpi

Multi-copying/stack/sort
Makes up to 999 copies of each
page / stacks or sorts

**Enlargement/reduction
Ratio**
Reduce or Increase document
sizes from 25% to 400% in 1%
increments

N in 1 copying
Allows the user to compress
2 or 4 pages on to a single
A4 sheet

2 in 1 ID copying

Allows the user to copy both
sides of an ID card to a single
A4 sheet

Grey scale
256 shades of grey
(8 bit for each colour)

Enlarge text copy⁸
Makes reading copied
documents easier if the size of
the text on the original
document is small

Scan

Scanner type
Contact Image Sensor (CIS)

**Colour and mono
scanning**
Yes

Scan speed (A4)¹²
1-sided: 25ipm
mono and colour

Scan speed (A3)¹²
1-sided: 13ipm/ppm mono
and colour

Scan resolution from ADF
600 x 600dpi (mono)
300 x 600dpi (colour)

**Scan resolution from
scanner glass**
1200 x 2400dpi (mono)
1200 x 1200dpi (colour)

**Interpolated scan
resolution**
Up to 19200 x 19200dpi

Colour depth
48 bit colour processing (input)
24 bit colour processing (output)

Grey scale
16 bit colour processing (input)
8 bit colour processing (output)

Scanner functions

Scan to e-mail
Scan and share documents via
e-mail server

Scan to OCR
Scan documents directly
into your word processing
application for instant editing

Scan to image
Scan into your preferred image
editing software

Scan to file
Scan to a file on your computer

Scan to network folder⁴
Scan documents to a nominated
folder on your network without
using a Windows PC

Scan to FTP
Scan documents directly to a
FTP server

Scan profile³
Create up to 5 preset network,
FTP profiles for an easy way to
store multiple scan settings

Scan to Microsoft Office
Scan to Word (.docx),
PowerPoint (.pptx), Excel (.xlsx)
for Microsoft Office

Scan to SharePoint⁴
Scan documents directly into
SharePoint (On-premise)

Scan to searchable PDF⁷
Scan documents to searchable
PDF files

Auto deskew³
Yes

Base colour removal³
Yes

Scanner drivers

Windows

TWAIN and WIA
Windows 10
(32 and 64 bit editions)
Windows 8.1
(32 and 64 bit editions)
Windows 7
(32 and 64 bit editions)
Windows Server 2008
R2/2012/2012 R2/2016/2019
(64 bit editions)

Linux⁵

SANE (32 and 64 bit editions)

Fax

Fax modem

33600bps (Super G3)

PC-fax send^{3&8} and receive^{4&8}

Send and receive faxes directly from your PC

Memory transmission

Up to 150 pages
(ITU-T Test Chart, standard resolution, JBIG)

Out of paper reception

Up to 150 pages (ITU-T Test Chart, standard resolution, JBIG)

Distinctive ring detection

(UK and Denmark only)

An external service that allows two or more telephone numbers shared on a single fixed line and use different ring tones

Error correction mode

(ECM)

Detect line errors during fax transmission and resend the page(s) of the document that had an error (recipient machines must share this feature for it to work)

Auto reduction

When receiving a single page document longer than A4 (297mm) the fax machine will automatically reduce the message to fit onto a single A4 sheet

Broadcasting

Send the same fax message up to 250 locations

Grey scale

256 shades (8 bit) of grey are available for faxing

Fleet management tools

Unattended installer⁴

Ability to centrally deploy and customise our drivers and software

MSI installer⁴

Modular installers that can be distributed through On-premise Active Directory[®]

BRAdmin^{4&5}

LAN/WAN management software

Embedded web server

Web based print management software embedded onto the device

Driver deployment

Wizard^{4&5}

Easily create print drivers for hassle free deployment over your network

Software

Brother iPrint&Scan desktop^{3&5}

Print from, scan to, send faxes, preview received faxes, preview copies and check the machine status from Windows or macOS PC

Security and network

Wired network

10Base-T/100Base-TX

Wired network security

APOP, SMTP-AUTH, SSL/TLS (IPPS, HTTPS, FTPS, SMTP, POP3, IMAP4), SNMP v3 802.1x (EAP-MD5, EAP-FAST, PEAP, EAP-TLS, EAP-TTLS), Kerberos, IPsec

Wireless network

2.4GHz: IEEE 802.11 b/g/n (Infrastructure Mode)
IEEE 802.11 g/n (Wi-Fi Direct)

5GHz: IEEE 802.11 a/n (Infrastructure Mode)
IEEE 802.11 a/n (Wi-Fi Direct)

Wireless network security

WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (TKIP/AES), WPA3-SAE (AES)
*Wi-Fi Direct supports WPA2-PSK (AES) only.
APOP, SMTP-AUTH, SSL/TLS (IPPS, HTTPS, FTPS, SMTP, POP3, IMAP4), SNMP v3, 802.1x (EAP-FAST, PEAP, EAP-TLS, EAP-TTLS), Kerberos, IPsec

Wi-Fi Direct™

Print wirelessly without having to go through a wireless access point (both automatic and manual methods supported)

Wireless setup support

Wi-Fi Protected Setup (WPS)

Wireless applications

Vertical Pairing

IPv4

ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS name resolution, DNS Resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/ Port9100, IPP, FTP Client ,FTP Server, SNMPv1/v2c/v3, TFTP server, POP3/IMAP4/SMTP Client, ICMP, Web Services (Print/Scan), CIFS Client, SNTP Client, LDAP, HTTP Server

IPv6

NDP, RA, mDNS, LLMNR Responder, DNS Resolver, LPR/LPD, Custom Raw Port/ Port9100, IPP, FTP Client, FTP Server, SNMPv1/v2c/v3, TFTP server, Web Services (Print/ Scan), POP3/IMAP4, SMTP Client, CIFS Client, SNTP Client, LDAP, ICMPv6, HTTP Server

IP Filter

Restrict which network users can or cannot access the device over the network (IPv4 only)

E-mail notifications

Automatically have the device send e-mail alerts when it requires attention, such as when the ink is low or needs replacing

E-mail reports

Receive usage reports on a regular basis via e-mail

Secure function lock 3.0

Restrict access to individual or groups of users over a network. Can be used with PC user login names for up to 100 users

Supplies and accessories

Standard yield cartridges¹

LC422BK - 550 pages
LC422C - 550 pages
LC422M - 550 pages
LC422Y - 550 pages
LC422VAL- 4 x 550 pages

High yield cartridges¹

LC422XLBK - 3,000 pages
LC422XLC - 1,500 pages
LC422XLM - 1,500 pages
LC422XLY - 1,500 pages
LC422XLVAL- 3,000 pages BK, 1,500 pages CMY

Note: product is shipped with LC422 standard cartridges¹³

Address book

LDAP

The ability to connect to an external LDAP enabled address book, like Microsoft Exchange

Dimensions and weights

With carton (WxDxH)
681 x 561 x 423mm - 22.6kg

Without carton (WxDxH)
576 x 477 x 305mm - 19.8kg

Duty cycle

Recommended monthly⁶

250 to 2,500 pages monthly print volume

Environment

Power consumption

Copying: approx. 29W
Ready: approx. 5.0W
Sleep: approx. 0.9W
Power off: approx 0.03W

Sound pressure

PC printing (colour/mono):
approx. 50.0dB(A)

Sound power

Mono: 6.54B(A)
Colour: 6.54B(A)

GS mark

Yes

TEC value

0.17 kWh/week

Ink save mode

This reduces the ink usage and
helps to reduce the total cost of
printer ownership