



## imagePROGRAF TM-240

# PERFORMANCE REIMAGINED

Reimagine printing performance with the sustainable 24" imagePROGRAF TM-240, offering less noise printing, more intuitive functionality and brilliant image quality. Seamlessly produce sharp, crisp lines and vivid red colour for eye-catching marketing materials and accurate CAD prints for AEC offices, retail and education.

- **Enhanced professional quality**

The new magenta ink produces a more brilliant red and stable image enhancements mean crisper lines. Print vivid and accurate CAD drawings, posters, educational materials and more

- **Reliable productivity**

Productivity that you can count on, with reliable performance, faster processing time and a quick return from sleep mode. Save time trimming excess margins with borderless print, giving full bleed images of any size, straight from the device

- **Intuitive functionality**

Functional design with a 4.3" touch screen panel displaying intuitive instructions and important information, like media type, remaining media and ink amount. Roll paper can be replaced with ease on the flat-top cover

- **Improved sustainability**

Environmentally conscious EPEAT Gold\* rated device for low energy consumption, with power reduction during standby and packaging free from polystyrene foam. Less noise printing makes it ideal for quiet offices

\*EPEAT Gold registered in the U.S.

**Canon**

# TECHNICAL SPECIFICATIONS

# imagePROGRAF TM-240

<b>PRINTER TECHNOLOGY</b>		<b>Margins Printable area</b>	
<b>Printer Type</b>	5 Colours 24"	Roll paper: Top: 3mm, Bottom: 3mm, Side: 3mm Roll paper (borderless): Top: 0mm, Bottom: 0mm, Side: 0mm Cut sheet (AppleAirPrint): Top: 3mm, Bottom: 12.7mm, Side: 3mm Cut sheet (Others): Top: 3mm, Bottom: 20mm, Side: 3mm	
<b>Print Technology</b>	Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head)	Roll Paper: One roll Cut Sheet: 1 sheet	
<b>Print Resolution</b>	2,400 x 1,200 dpi	[Recommended] 515mm(JIS B2), 728mm(JIS B1), 594mm (ISO A1), 10", 14", 17", 24"	
<b>Number of Nozzles</b>	Total : 15360 nozzles MBK : 5120 nozzles BK, C, M, Y: 2560 nozzles each	[Printable] 257mm(JIS B4), 297mm (ISO A3), 329mm (ISO A3+), 420mm (ISO A2), 515mm (JIS B3), 8", 12", 15", 16", 18", 20", 22", 300mm, 500mm, 600mm	
<b>Line Accuracy</b>	±0.1% or less User adjustments necessary. Printing environment and media must match those used for the adjustments.	Other than above, free size borderless printing is supported on only roll paper by user definition	
<b>Nozzle Pitch</b>	1,200 dpi x 2 lines	Standard position - 1 sheet	
<b>Ink Droplet Size</b>	minimum 5pl per colour		
<b>Ink Capacity</b>	Bundled Starter Ink: 300ml (80ml for MBK, 55mlx4 for BK, C, M, Y) Sales Ink: 55ml (MBK, BK, C, M, Y)		
<b>Ink Type</b>	Pigment inks : 5 colours: MBK/BK/C/M/Y		
<b>OS Compatability</b>	32 Bit: Windows7, Windows 8.1, Windows 10 64 Bit: Windows 7, Windows 8.1, Windows 10, Windows 11, Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022 Apple Macintosh: macOS 10.15.7-macOS 13	<b>POWER AND OPERATING REQUIREMENTS</b>	
<b>Others supported job submission protocol</b>	Apple AirPrint	<b>Power Supply</b>	AC 100-240V (50-60Hz)
<b>Printer Languages</b>	HP-GL/2, HP RTL, JPEG (Ver. JFIF 1.02), CALS G4 (submission via FTP only)	<b>Power Consumption</b>	Operation: 59W or less Sleep mode: 2.2W or less Default setting for the time to enter the Sleep mode: Approx. 5 minutes Power off: 0.1W or less
<b>Standard Interfaces</b>	USB A Port: N/A USB B Port: Hi-Speed USB Ethernet: IEEE802.3ab(1000base-T), IEEE802.3u(100BASE-TX)/IEEE802.3 (10BASE-T) Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b	<b>Operating Environment</b>	Temperature: 15-30°C, Humidity: 10-80% RH (no dew condensation) Operation: Approx. 39dB(A) (Standard Plain Paper, Standard mode, Line Drawing/Text mode) (Measured based on ISO7779 standard)
	*Please refer to user manual how to activate/deactivate the wireless LAN	<b>Acoustic Noise (Power/Pressure)</b>	Standby: 35 dB(A) or less Operation: 6.0 Bels or less (Standard Plain Paper, Standard mode, Line Drawing/Text mode) (Measured based on ISO7779 standard)
<b>MEMORY</b>		<b>Regulations</b>	CE mark, UKCA mark
<b>Standard Memory</b>	2GB	<b>Environment Certificates</b>	CB certification, EPEAT GOLD <sup>1</sup>
<b>Hard Drive</b>	Expansion slot : No		
	N/A		
<b>PRINTING SPEED</b>		<b>DIMENSIONS AND WEIGHT</b>	<b>W x D x H</b>
<b>CAD Drawing</b>		<b>Physical Dimensions and Weight</b>	Main unit + Stand + Basket (SD-24) 978 x 868 x 1060 mm (Operation panel is not tilted up/Basket Opened)
<b>Plain paper (A1):</b>	0:23 (Fast Economy Model) 0:25 (Fast) 0:51 (Standard)		978 x 756 x 1060 mm (Operation panel is not tilted up/Basket Closed)
<b>Poster:</b>			50.9 kg (including Roll Holder Set, excluding ink and print head)
<b>Plain Paper (A1):</b>	0:25 (Fast Economy Model) 0:25 (Fast) 0:49 (Standard)	<b>Packaged Dimensions and Weight</b>	Printer (Main unit with pallet): 1152 x 912 x 679 mm, 71kg Stand + Basket (SD-24): 1058 x 826 x 270 mm, 20kg
<b>Heavy coated paper (A1):</b>	0:56 (Fast) 1:45 (Standard)		
<b>MEDIA HANDLING</b>		<b>WHAT'S INCLUDED</b>	
<b>Media Feed and Output</b>	Roll Paper : One Roll, Upper-loading, Front Output Cut Sheet : Upper-loading, Front Output (Manual feed using media locking lever)	<b>What's in the Box?</b>	Printer, 1 Print head, Power Cable, 1 Set of starter ink tanks, Installation Guide, Safety/Standard Environment leaflet, LFP Eur Address Sheet, Important Information Sheet, Notice for PosterArtist WEB
<b>Media Width</b>	Roll paper: 203.2 - 610mm Cut sheet: 210 - 610mm	<b>Software Included</b>	Software available as Download from Web
<b>Media Thickness</b>	Roll/Cut : 0.07mm - 0.8mm		
<b>Minimum Printable Length</b>	Roll paper: 203.2mm Cut sheet: 279.4mm		
<b>Maximum Printable Length</b>	Roll paper : 18m (varies according to the OS and application) Cut sheet : 1.6m	<b>OPTIONS</b>	Stand Basket (Simple Basket): SD-24 2"/3" Roll Holder: RH2-28 IC Card Reader Holder: RA-02
<b>Maximum Media Roll Diameter</b>	150 mm	<b>Optional Items</b>	
<b>Media Core Size</b>	Internal diameter of roll core: 2"/3" (Optional)	<b>CONSUMABLES</b>	
<b>Margins Recommended area</b>	Roll paper: Top: 20mm, Bottom: 3mm, Side: 3mm Cut sheet(AppleAirPrint): Top:20mm, Bottom: 31mm, Side: 3mm Cut sheet (Others): Top: 20mm, Bottom:20mm, Side:3mm	<b>User Replaceable Items</b>	Ink Tank: M: PFI-031(55ml), MBK/BK/C/Y:PFI-030(55ml) Print Head: PF-06 Cutter Blade: CT-08 Maintenance Cartridge: MC-31

<sup>1</sup> EPEAT Gold registered in the U.S.

## Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.<sup>2</sup> and <sup>3</sup> All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.



Canon

E | [sales@designsupply.com](mailto:sales@designsupply.com)  
T | 020 7842 1555 W | [www.designsupply.com](http://www.designsupply.com)  
Unit 2, Green Lane Business Centre, New Eltham, London, SE9 3TL