



imagePROGRAF TM-250 / TM-255

Est. 1991  
**DESIGNSUPPLY**  
supporting creativity

# PERFORMANCE REIMAGINED

Elevate printing experiences with enhanced productivity, intuitive functionality and professional image quality from a sustainable device. The 24" printer can seamlessly create accurate CAD prints with sharp lines and eye-catching marketing materials, designed for corporate and sizable AEC offices and the retail and education sector.

- **Professional printing quality**

Use stable image enhancements to create sharp, crisp lines and new magenta ink for vivid red colour. As a result, you'll produce vivid and accurate CAD drawings, posters and educational materials

- **Enhanced productivity**

Produce A1 CAD prints in just 20 seconds, or A1 posters in 22 seconds. Save time trimming excess margins with borderless prints of any sizes and easily meet higher print demand with larger ink tanks, quick processing time and a fast return from sleep mode

- **Intuitive functionality**

Follow easy instructions and take in important information like media type, remaining media and ink amount on a 4.3" touch screen panel. Save time by setting roll paper with quick access through a flat-top cover

- **Improved sustainability**

Environmentally conscious EPEAT Gold\* rated device for low energy consumption, with power reduction during standby and packaging free from polystyrene foam. Less noise printing makes it ideal for quiet offices

\*EPEAT Gold registered in the U.S.

**Canon**

# TECHNICAL SPECIFICATIONS

# imagePROGRAF TM-250 / TM-255

PRINTER TECHNOLOGY	TM-250	TM-255	TM-250	TM-255
Printer Type	5 Colours 24"	5 Colours Printable area	Roll paper: Top: 3mm, Bottom: 3mm, Side: 3mm Roll paper (borderless): Top: 0mm, Bottom: 0mm, Side: 0mm Cut sheet (AppleAirPrint): Top: 3mm, Bottom: 12.7mm, Side: 3mm Cut sheet (Others): Top: 3mm, Bottom: 20mm, Side: 3mm	
Print Technology	Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head)	Media Feed Capacity	Roll Paper: One roll Cut Sheet: 1 sheet	
Print Resolution	2,400 x 1,200 dpi	Media Take-Up Roll Unit	N/A	
Number of Nozzles	Total: 15360 nozzles MBK: 5120 nozzles BK, C, M, Y: 2560 nozzles each ±0.1% or less	Borderless Printing Width (Roll Only)	[Recommended] 515mm(JIS B2), 594mm (ISO A1), 10", 14", 17", 24" [Printable] 257mm(JIS B4), 297mm(ISO A3), 329mm (ISO A3+), 420mm(ISO A2), 515mm(JIS B3), 8", 12", 15", 16", 18", 20", 22", 300mm, 500mm, 600mm	
Line Accuracy	User adjustments necessary. Printing environment and media must match those used for the adjustments. ±0.1% or less	Maximum number of delivered prints	Other than above, free size borderless printing is supported on only roll paper by user definition Standard position: 1 sheet Folding position: Plain paper 20 sheets on A1 portrait Flat position: Plain paper 20 sheets on A2 landscape (exclude strong curled position)	
Nozzle Pitch	1,200 dpi x 2 lines	POWER AND OPERATING REQUIREMENTS	AC 100-240V (50-60Hz)	
Ink Droplet Size	minimum 5pl per colour	Power Supply	Operation: 62W or less Sleep mode: 2.2W or less	
Ink Capacity	Bundled Starter Ink: 490ml (130ml for MBK, 90ml x 4 for BK, C, M, Y) Sales Ink: 300/130ml (MBK, BK, C, M, Y)	Power Consumption	Default setting for the time to enter the Sleep mode: Approx. 5 minutes Power off: 0.1W or less	Operation: 64W or less Sleep mode: 2.2W or less
Ink Type	Pigment inks : 5 colours MBK/BK/C/M/Y	Operating Environment	Temperature: 15-30°C, Humidity: 10-80% RH (no dew condensation)	Default setting for the time to enter the Sleep mode: Approx. 5 minutes Power off: 0.1W or less
OS Compatability	32 Bit: Windows 7, Windows 8.1, Windows 10 64 Bit: Windows 7, Windows 8.1, Windows 10, Windows 11, Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022 Apple Macintosh: macOS 10.15.7-macOS 13	Acoustic Noise (Power/Pressure)	Operation: 41dB(A), (Standard Plain Paper, Standard mode, Line Drawing/Text mode) (Measured based on ISO7779 standard)	CE mark, UKCA mark CB certification, EPEAT GOLD <sup>1</sup>
Others supported job submission protocol	Apple AirPrint	Regulations	Standby: 35 dB(A) or less Operation: 6.2 Bel or less (Standard Plain Paper, Standard mode, Line Drawing/Text mode) (Measured based on ISO7779 standard)	
Printer Languages	HP-GL/2, HP RTL, JPEG (Ver. JIF 1.02), CALS G4 (submission via FTP only)	Environment Certificates	CE mark, UKCA mark CB certification, EPEAT GOLD <sup>1</sup>	
Standard Interfaces	USB A Port: N/A  USB B Port: Hi-Speed USB Ethernet: IEEE802.3ab(1000base-T), IEEE802.3u (100BASE-TX)/IEEE802.3 (10BASE-T) Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b	DIMENSIONS AND WEIGHT	W x D x H Main unit with stand 978 x 885 x 1060 mm (Operation panel is not tilted up/Basket Opened)	
MEMORY	2GB Expansion slot: No	Physical Dimensions and Weight	978 x 756 x 1060 mm (Operation panel is not tilted up/Basket Closed)	
Standard memory	128GB (Physical memory 2GB) Expansion slot : No	Packaged Dimensions and Weight	55 kg (including Roll Holder Set, excluding ink and print head)	
Hard Drive	N/A	WHAT'S INCLUDED	Printer (Main unit with stand and pallet): 1152 x 913 x 946 mm, 96kg	
PRINTING SPEED		What's in the Box?		
CAD Drawing		Software Included	Printer, Printer Stand, 1 Print head, Power Cable, 1 Set of starter ink tanks, Installation Guide, Safety/Standard Environment leaflet, LFP Eur Address Sheet, Important Information Sheet, Stack Printer Stand Setup Guide, Notice for PosterArtist WEB	
Plain Paper (A1)	0:20 (Fast Economy Mode) 0:23 (Fast) 0:40 (Standard)		Software available as Download from Web	
Poster:				
Plain Paper (A1)	0:22 (Fast Economy Mode) 0:25 (Fast) 0:44 (Standard)			
Heavy coated paper (A1)	0:55 (Fast) 1:23 (Standard)			
MEDIA HANDLING				
Media Feed and Output	Roll Paper : One Roll, Upper-loading, Front Output Cut Sheet : Upper-loading, Front Output (Manual feed using media locking lever)			
Media Width	Roll paper: 203.2 - 610mm Cut sheet: 203.2 - 610mm			
Media Thickness	Roll/Cut : 0.07mm - 0.8mm			
Minimum Printable Length	Roll paper: 203.2mm Cut sheet: 279.4mm			
Maximum Printable Length	Roll paper : 18m (varies according to the OS and application) Cut sheet : 1.6m			
Maximum Media Roll Diameter	150 mm			
Media Core Size	Internal diameter of roll core: 2" / 3"			
Margins Recommended area	Roll paper: Top: 20mm, Bottom: 3mm, Side: 3mm Cut sheet (AppleAirPrint): Top: 20mm, Bottom: 31mm, Side: 3mm Cut sheet (Others): Top: 20mm, Bottom: 20mm, Side: 3mm			

## Footnotes

<sup>1</sup> EPEAT Gold registered in the U.S.

## Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.<sup>TM</sup> and <sup>®</sup>. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.



E | sales@designsupply.com

T | 020 7842 1555 W | www.designsupply.com

Unit 2, Green Lane Business Centre, New Eltham, London, SE9 3TL